

APPROVALS AND SPECIFICATIONS

- ASTM A135, Grade A
- ASTM A795, Type E, Grade A
- Pressure rated to 300 psi
- Underwriters Laboratories—United States of America
- Underwriters Laboratories—Canada
- Factory Mutual
- NFPA-13
- NFPA-13R
- NFPA-14
- Made in the United States of America
- UL, ULC & FM listed for roll-groove, plain-end and welded joints for wet, dry, preaction and deluge sprinkler systems.
- LEED v4 EPD Certified

FINISHES AND COATINGS

- Eddythread Sprinkler Pipe receives a UV coating which has corrosion protection expected with a painted carbon steel product, i.e. it would be expected to resist corrosion for an extended and indefinite period in a clean and dry environment and, as environmental conditions deteriorate, the corrosion protection would also diminish.
- Eddythread Sprinkler Pipe (black) receives an ID mill coating of Eddy Guard II MIC preventative coating. FM Approved for use with CPVC. EG2 has been tested at independent laboratories to resist bacterial growth and maintain minimal bacterial count after multiple flushes (25) of the pipe.
- Eddythread Sprinkler Pipe when Hot Dip Galvanized by ASTM A123 and supplied by Bull Moose Tube is UL listed and FM approved.

PRODUCT IDENTIFICATION

- Every length of Bull Moose fire sprinkler pipe features large, easy-to-read, continuous stenciling, clearly identifying the manufacturer, type of pipe, size, length, and heat number.

Nominal Pipe Size (inches)	1	1-1/4"	1-1/2"	2"
O.D. (in)	1.295	1.650	1.900	2.375
I.D. (in)	1.083	1.418	1.645	2.123
Nom. Wall Thickness (in)	0.106	0.116	0.128	0.126
Empty Weight (lb/ft)	1.347	1.902	2.416	3.029
Water Filled Weight (lb/ft)	1.746	2.586	3.337	4.563
C.R.R. *	1.00	1.00	1.00	1.00
Pieces per Lift	70	51	44	30

*Calculated using Standard UL CRR formula, UL Fire Protection Directory, Category VIZY



SUBMITTAL INFORMATION

Project

Contractor

Engineer

Specification Reference

Date System Type

Locations

Comments

☐ Eddythread - Black ☐ Eddythread - Hot Dip Galvanized